


LightStack® Surface Mount Fiber Enclosure


The Simon LightStack Surface Mount Fiber Enclosure houses a single LightStack MTP to LC Module or an LC or MTP pass through adapter plate. Ideal for fiber distribution in a variety of tight spaces, the LightStack Surface Mount Enclosure can be easily mounted to walls, under floors or above the ceiling. It supports an optional splice accessory for fusion splicing and cable slack storage. The LightStack Surface Mount Fiber Enclosure enables the deployment of fiber consolidation points or zone distribution points that simplify moves, adds and changes by significantly reducing installation time and disruption. Rather than longer home run cabling links, MTP plug and play fiber assemblies can easily connect to the enclosure and then shorter MTP or LC fiber assemblies are used to connect from the enclosure to devices. For example, the LightStack Surface Mount Enclosure is ideal for placement under the floor to connect to banks of slot machines in a casino environment. It can also be used in passive optical network applications to distribute fiber from MTP splitters to optical network terminals or in other FTTX applications.



Optional Splice Enclosure – Mounts below main enclosure for managing slack and protecting single or mass fusion splices.




Mounting Applications – Mounts easily in tight spaces (e.g., under raised floors) for distributing fiber in a variety of applications and environments.



Plug and Play – LightStack MTP to LC module (not included) accepts an MTP trunk cable at the rear for fast deployment and pathway space savings.

Ordering Information

Part #
LSE-01 **Description**
LightStack Surface Mount Module Enclosure,
accepts one (1) LightStack module/adaptor plate



Module Enclosure

Part #
LSS-01 **Description**
LightStack Surface Mount Splice Enclosure, supports slack storage
and up to 12 standard splices or up to 72 mass fusion splices



Splice Enclosure

	Module Enclosure	Splice Enclosure
Height	18mm (0.7 in.)	32mm (1.3 in.)
Width	119mm (4.7 in.)	119mm (4.7 in.)
Length	179mm (7.0 in.)	194mm (7.7 in.)
Weight	0.57kg (1.25 lb)	0.68kg (1.5 lb)
Color	Black	Black
Material	Cold rolled steel	Cold rolled steel

**Worldwide Headquarters
North America**
Watertown, CT USA
Phone (1) 860 945 4200 US
Phone (1) 888 425 6165

**Regional Headquarters
EMEA**
Europe/Middle East/Africa
Surrey, England
Phone (44) 0 1932 571771

**Regional Headquarters
Asia/Pacific**
Shanghai, P.R. China
Phone (86) 21 5385 0303

**Regional Headquarters
Latin America**
Bogota, Colombia
Phone (571) 657 1950

**Siemon Interconnect
Solutions**
Watertown, CT USA
Phone (1) 860 945 4213 US
www.siemon.com/SIS