

# MAX® PATCH PANELS

MAX patch panels provide a flexible, high density modular termination solution for the datacenter and telecommunications room. Using the full line of UTP Z-MAX and MAX modules (available separately), the panel can be configured for a variety of multimedia applications. Blank modules can be used to reserve ports for future capacity.

**PATENTED**

**MODULAR PATCHING**

Panels can be mounted directly to fit a standard 19 inch relay rack or cabinet

Available in 16-, 24-, 48-, and 72-port configurations

Modules utilize Siemon's colored icons for easy identification and administration

Bold port numbering enables quick and ready identification of outlets

Write-on area provided for panel designation

Multimedia capability — mix and match many different types of connectors

Lightweight, high strength brushed aluminum with black protective finish

**Technical Tip!**  
Use flat MAX modules for patch panel applications



Individual modules snap into place from front or rear of panel for added installation flexibility

Removable designation labels can be laser printed and enable proper circuit identification for each port

Rear cable management bar included for routing horizontal cables to terminations

## ORDERING INFORMATION

### MAX® Series Patch Panels: Flat

- MX-PNL-16 .....16-port panel, 1 RMS
- MX-PNL-24 .....24-port panel, 1 RMS
- MX-PNL-48 .....48-port panel, 2 RMS
- MX-PNL-72 .....72-port panel, 2 RMS



### MAX® Series Patch Panels: Angled

Siemon's MAX series angled patch panels route cables directly into the vertical cable managers eliminating the need for horizontal cable management between panels.

- MX-PNLA-24 .....24-port angled panel, 1 RMS
- MX-PNLA-48 .....48-port angled panel, 2 RMS



Angled MAX panels are not recommended for use with RS3 rack series. Use the RS series racks.  
 Note: 1 RMS = 44.5mm (1.75 in.)

### S89D Bracket:

The MAX S89D offers an economical solution for smaller applications while allowing for a range of different media using the full line of MAX modules.

- MX-89D-12.....12-port Max panel mounted on an 89D bracket



### Labeling Accessories:

- MX-PNL-LBL4\*\* .....10 sheets of laser printable labels for 16-port MAX panel
- MX-PNL-LBL6\*\* .....10 sheets of laser printable labels for 24- and 48-port MAX panel

\*\*Visit our web site or contact our Technical Support Department for labeling software.

### Reusable Hook and Loop Cable Managers:

- VCM-25-(XXX)-(X) .....Roll of 25 cable managers
  - VCM-250-(XXX)-(X) .....Spool of 250 cable managers
- Use (XXX) to specify length:  
 06 = 152mm (6 in.), holds 51mm (2 in.) diameter cable bundle  
 12 = 305mm (12 in.), holds 102mm (4 in.) diameter cable bundle  
 18 = 457mm (18 in.), holds 153mm (6 in.) diameter cable bundle
- Use (X) to specify color: 1 = black, 2 = white, 3 = red, 4 = gray, 5 = yellow, 6 = blue, 7 = green, 9 = orange

### For related product information request Spec Sheet(s):

- MAX Modules Tool-less (PROD-SS-MXM)
- MAX 5e Module Punch-down (PROD-SS-MPD)
- MAX 6 Modules (PROD-SS-MX6)

Because we continuously improve our products, Siemon reserves the right to change specifications and availability without prior notice.  
 MAX® and TERA® are trademarks of Siemon

**North America**  
 Watertown, CT USA  
 Phone (1) 860 945 4200 US  
 Phone (1) 888 425 6165 Canada

**Europe/Middle East/Africa**  
 Surrey, England  
 Phone (44) 0 1932 571771

**Asia/Pacific**  
 Shanghai, P.R. China  
 Phone (86) 21 5385 0303

**Latin America**  
 Bogota, Colombia  
 Phone (571) 657 1950