



Metered Vertical PDU

Part # 8TV33-BA24E-K1A.....	Description PDU,METER,VERT,C20,IEC,24XC13,6XC19,230V/16A
---------------------------------------	--

SPECIFICATIONS

Physical Properties	
Dimensions	1680.5 x 68 x 44.4mm (66.2 x 2.677 x 1.748in.)
Orientation	Vertical
Footprint	Zero U tool-less button mounting
Mounting Method	Center to Center Spacing 1555.75mm (61.25in.)
Case Material	Aluminum
Case Color	Black
Shipping Weight	4kg

Electrical Properties	
Voltage	230VAC
Current	16A
Frequency	50/60 Hz
Input Plug	C20
Plug Cable Color	Black
Input Cable Wire Gauge	3x14AWG
Input Cable Length	3.0m (10ft) (±76.20mm)(±3.0in.)
Power Entry Cable Length	Bottom Entry
Output Socket #1	24/Black x C13
Output Socket #1 Voltage	230VAC
Output Socket #2	6/Black x C19
Output Socket #2 Voltage	230VAC
Load Capacity	3680VA (3.68kW)
Circuit Protection	16A 1-Pole Breaker

Environmental	
Temperature Operating Range	10-45°C / 50-113°F
Relative Humidity Min	5%
Relative Humidity Max	95%
Elevation	0-3000m

Safety	
Certification/Agency Approvals	IEC/EN 60950-1
Certification/Agency Approvals	EN 55022 Class A
Certification/Agency Approvals	EN 55024
Certification/Agency Approvals	EN 61000-3-2
Certification/Agency Approvals	EN 61000-3-3
Certification/Agency Approvals	RoHS
Certification/Agency Approvals	REACH

Metering Accuracy	
Meter Accuracy	+/-1% (Unless Otherwise Specified)

General Functions	
Built in Display	LCD Display
Hard Reboot Button	Yes
Measurement Level	V, A

Worldwide Headquarters
North America
Watertown, CT USA
Phone (1) 860 945 4200 US
Phone (1) 888 425 6165

Regional Headquarters
Europe/Russia/Africa
Chertsey, Surrey, England
Phone (44) 0 1932 571771

Regional Headquarters
China
Shanghai, P.R. China
Phone (86) 21 5385 0303

Regional Headquarters
Latin America
Bogota, Columbia
Phone (571) 657 1950

Regional Headquarters
India / Middle East
Dubai, United Arab Emirates
Phone (971) 43689743

Regional Headquarters
Asia Pacific
Sydney, Australia
Phone (61) 28977 7500