




## CATEGORY 8.2 E20 CABLE (Global)

Siemon's Category 8.2 cable exceeds the transmission performance requirements of IEC 61156-9 up to 2000 MHz. This fully shielded cable supports 30-meter Class II channels to meet IEEE 802.3bq 25 Gb/s (25GBASE-T) and 40 Gb/s (40GBASE-T) applications in the data center. As part of a Class II twisted-pair cabling system which shares open and common specifications, interoperability and backwards compatibility are ensured with the reach to support a broad range of architectures for switch-to-server connections, including middle of row (MoR) and end of row (EoR) deployments. With a cable jacket qualified for mechanical reliability in high temperature environments up to 75°C, Siemon's S/FTP Category 8.2 cable features individual foils around each pair and a high screen coverage outer braid to provide superior noise immunity and coupling attenuation performance.




### CABLE FEATURES:

- S/FTP
- LSOH Nominal Jacket OD: 8.3 (0.327 in.)
- CMR Nominal Jacket OD: 8.5 (0.335 in.)
- 22 AWG 0.63 (0.025 in.) solid bare copper
- Pairs individually shielded with aluminum bonded polyester tape
- 75° temperature rating

### STANDARDS COMPLIANCE:

- ISO/IEC 11801-1
- EN 50173-1
- IEC 61156-9
- UL CMR
- LSOH: IEC 60332-1, IEC 60332-3-22, IEC 61034, IEC 60754,
- LSOH: EN 50575 Class Dca, s2, d2, a1



### APPLICATIONS SUPPORT

- 10BASE-T to 40GBASE-T
- IEEE 802.3 af (Type 1 PoE)
- IEEE 802.3 at (Type 2 PoE)
- IEEE 802.3 bt (Type 3 PoE)
- IEEE 802.3 bt (Type 4 PoE)
- Power Over HDBaseT (PoH)





# PRODUCT INFORMATION

## ELECTRICAL SPECIFICATIONS

DC Resistance	< 2.1 Ω/30m
DC Resistance Unbalance	within pairs ≤ 2%
	between pairs ≤ 5%
NVP	74%
TCL	≥ 50-15 x log (f)dB
Delay Skew	≤ 7.5ns/30m

## PHYSICAL PROPERTIES

	LSOH	CMR
Pulling Tension (max)	110N (25 lbf)	110N (25 lbf)
Bend Radius (min)	66.4mm (2.61 in.)	68mm (2.67 in.)
Installation Temperature	0 to 75°C (32 to 167°F)	0 to 75°C (32 to 167°F)
Storage Temperature	-20 to 75°C (-4 to 167°F)	-20 to 75°C (-4 to 167°F)
Operating Temperature	-20 to 75°C (-4 to 167°F)	-20 to 75°C (-4 to 167°F)

## TRANSMISSION PERFORMANCE

GUARANTEED WORST CASE
  SIEMON TYPICAL

Frequency (MHz)	Insertion Loss (dB/30m)		NEXT (dB)		PS NEXT (dB)		ACR (dB)		PSACR (dB)		ACR-F (dB)		PS ACR-F (dB)		Return Loss (dB)		Propagation Delay (ns)	
	Guaranteed	Typical	Guaranteed	Typical	Guaranteed	Typical	Guaranteed	Typical	Guaranteed	Typical	Guaranteed	Typical	Guaranteed	Typical	Guaranteed	Typical	Guaranteed	Typical
1	1.1	0.7	78.0	80.9	75.0	88.0	76.9	80.2	73.9	87.4	78.0	85.6	75.0	84.1	20.0	21.6	171.0	144.0
4	1.1	1.1	78.0	91.3	75.0	96.2	76.9	90.2	73.9	95.1	78.0	92.7	75.0	90.7	23.1	31.8	165.4	140.0
10	1.8	1.6	78.0	99.6	75.0	96.2	76.2	98.0	73.2	94.6	78.0	97.3	75.0	95.5	25.0	35.9	163.4	138.0
16	2.2	2.1	78.0	101.0	75.0	89.6	75.8	98.9	72.8	87.5	76.5	101.0	73.5	95.8	25.0	29.8	162.8	137.0
20	2.5	2.3	78.0	98.1	75.0	96.5	75.5	95.8	72.5	94.2	74.7	95.9	71.6	94.2	25.0	30.6	162.5	137.0
31.25	3.2	3.0	78.0	98.2	75.0	97.9	74.8	95.2	71.8	94.9	70.7	95.2	67.7	92.5	25.0	30.2	162.0	136.0
62.5	4.5	4.2	78.0	101.0	75.0	92.2	73.5	96.8	70.5	88.0	64.7	93.9	61.7	89.8	23.6	32.5	161.4	136.0
100	5.5	5.1	75.4	100.0	72.4	94.7	69.9	94.9	66.9	89.6	60.6	92.7	57.6	89.4	22.2	34.6	161.1	136.0
200	7.9	7.3	70.9	101.0	67.9	89.5	63.0	93.7	60.0	82.2	54.6	91.0	51.6	85.2	20.1	30.8	160.8	135.0
250	8.9	8.2	69.4	99.1	66.4	88.2	60.5	90.9	57.5	80.0	52.6	88.3	49.6	85.6	19.4	26.6	160.7	135.0
300	9.8	9.0	68.2	99.3	65.2	88.7	58.4	90.3	55.4	79.7	51.1	86.0	48.1	84.3	18.8	20.4	160.6	135.0
350	10.6	9.8	67.2	97.2	64.2	86.1	56.6	87.4	53.6	76.3	49.7	84.1	46.7	81.6	18.4	29.4	160.6	135.0
400	11.4	10.4	66.4	101.0	63.4	88.3	55.0	90.6	52.0	77.9	48.6	85.2	45.6	80.8	18.0	26.6	160.6	135.0
550	13.5	12.3	64.3	97.3	61.3	85.5	50.8	85.0	47.8	73.2	45.8	80.9	42.8	80.4	17.0	29.5	160.5	135.0
600	14.1	12.9	63.7	99.5	60.7	84.8	49.6	86.6	46.6	71.9	45.0	80.0	42.0	80.0	16.8	23.1	160.5	135.0
800	16.5	14.9	61.8	93.9	58.9	81.0	45.3	79.0	42.4	66.1	42.5	78.2	39.5	74.1	15.9	26.0	160.4	135.0
900	17.6	17.6	61.1	97.3	58.1	78.7	43.5	79.7	40.5	61.1	41.5	77.4	38.5	73.6	15.5	28.5	160.4	135.0
1000	18.6	16.7	60.4	96.1	57.4	79.9	41.8	79.4	38.8	63.2	40.6	76.5	37.6	72.7	15.2	32.7	160.3	135.0
1600	24.0	21.6	57.3	97.5	54.3	74.1	33.3	75.9	30.3	52.5	36.5	69.7	33.5	67.6	13.8	19.5	160.3	135.0
2000	27.2	24.6	55.9	87.9	52.9	64.9	28.7	63.3	25.7	40.3	34.6	64.2	31.6	63.3	13.1	19.4	160.3	135.0

All performance based on 30 meters

## Ordering Information:

Part #	Description
9T82L4-E2008R1A	LSOH (IEC 60332-3-22), Class Dca, s2, d2, a1 Violet Jacket, 305m, Reel
9T82R4-E2006R1A	CMR, Blue Jacket, 305m, Reel

Because we continuously improve our products, Siemon reserves the right to change specifications and availability without prior notice.

**Worldwide Headquarters**  
**North America**  
 Watertown, CT USA  
 Phone (1) 860 945 4200

**Regional Headquarters**  
**Europe Russia Africa**  
 Chertsy, Surrey, England  
 Phone (44) 0 1932 571771

**Regional Headquarters**  
**China**  
 Shanghai, P.R. China  
 Phone (86) 215385 0303

**Regional Headquarters**  
**Latin America**  
 Bogota, Colombia  
 Phone (571) 657 1950/51/52

**Regional Headquarters**  
**India Middle East**  
 Dubai, United Arab Emirates  
 Phone (971) 4 3689743

**Regional Headquarters**  
**Asia Pacific**  
 Sydney, Australia  
 Phone (86) 21 5385 0303

**Siemon Interconnect Solutions**  
**Watertown, CT USA**  
 Phone (1) 860 945 4213 US  
 www.siemon.com/SIS

